



DELTA-XERO
THE FUTURE IS SYSTEM RELIABILITY

DXO Powertrain Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to **0.1 µm**
- Designed for engine oil, diesel and kerosene
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
Extend oil drain intervals
- Minimised fluid oxidation
- Mitigation and reduction of varnish
- Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- **100% Recycled** media



Maintaining healthy fluid by removing:

- Abrasive material down to 0.1 µm
- Bacteria
- Water bound free and emulsified
- Oxidation products (Sludge and resin)
- Siloxane

Technical Specifications

Part No.	DXPT
Weight (Dry)	1.65 kg
Weight (Saturated)	Up to 4.0 kg (Fluid dependent)
Flow capacity	Up to 7 lpm (Viscosity dependent)
Water absorption, free & bound	Up to 2600 ml
Min and max limits	Min 0°C. Max 100°C
Material	PP Cellulose mix
Package dimensions	192 mm x 192 mm x 265 mm

© 2022 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



ایران - تهران - خیابان پاسداران بهستان هشتم
پلاک ۱ - برج آبتین، طبقه ۴ - واحد ۹
شماره تماس: ۰۲۱ ۷۳۶۸۴۰۰۰
info@rnaco.com



نماینده فروش و خدمات پس از فروش **DELTA-XERO** در ایران