

DXO Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to 0.1 μ
- Designed for mineral and synthetic fluids
- Hydraulic, lube and gear applications
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Minimised fluid oxidation
- Mitigation and reduction of varnish
- · Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- Small footprint
- 100% Recycled media

Maintaining healthy fluid by removing:

- Bacteria
- Water (free and emulsified)
- Oxidation products (Sludge and resin)



Technical Specifications

Part No.	DXO
Weight (Dry)	1.85 kg
Weight (Saturated)	Up to 4.5 kg
Flow capacity	1 lpm @ 32 cSt
Water absorption, free & bound	Up to 2600 ml
Min and max limits	Min o°C - Max 100°C
Material	PP Cellulose mix
Package dimensions	192 mm x 192 mm x 265 mm



© 2022 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only, and may be subject to change without prior notice



ایران-تهران-خیابان پاسداران بهستان هشتم پلاک ۱ - برج آبتین، طبقه٤ - واحد ۹ شماره تماس: ۳۲۶۸٤۰۰۰ info@rnaco.com

